

## Auto-feed Screwdriver

### 6842

470 W • 25 – 55 mm • 4 700 min<sup>-1</sup>

#### Quick screwdriving with auto-feed system for professionals

A screwdriver for screw strips with a speed of 4 700 min<sup>-1</sup> and a robust aluminium auto-feed system for 25-55 mm screws. A precise depth control switch and screw guide ensure accuracy and prevent slanted screw feeds.



**TECHNICAL**

### SPECIFICATIONS

|   |                         |
|---|-------------------------|
| MAXIMUM OUTPUT POWER                          | 470 W                   |
| POWER SUPPLY CORD                             | 4,0 m                   |
| SOUND POWER LEVEL (LWA)                       | 95 dB(A)                |
| SOUND PRESSURE LEVEL (LPA)                    | 84 dB(A)                |
| NOISE UNCERTAINTY (K FACTOR)                  | 3 dB(A)                 |
| VIBRATION LEVEL (3 AXES)                      | ? 2,5 m/s <sup>2</sup>  |
| WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003) | 2,0 kg                  |
| PRODUCT DIMENSIONS (L X W X H):               | 400 x 75 x 243 mm       |
| EAN   | 88381081955             |
| NO LOAD SPEED                                 | 4 700 min <sup>-1</sup> |
| BIT SIZE                                      | 157 x 5 mm              |
| CAPACITY DRYWALL SCREW                        | 4,0 mm                  |
| COLLATED DRYWALL SCREW                        | 25 - 55 mm              |

### USER BENEFITS

Link to Product page - <https://makitauae.com/product/6842-auto-feed-screwdriver/>