



# Random orbit sander

## BO5030

300 W • 125 mm

### ■ TECHNICAL

#### Excellent working access from a vertical frame structure

Eccentric sander with excellent workmanship thanks to its balanced structure and chamfered grips. Dust extraction in a paper bag. The grinding pad has a diameter of 125 mm

### SPECIFICATIONS

MAXIMUM OUTPUT POWER	300 W
POWER SUPPLY CORD	2,0 m
■ SOUND POWER LEVEL (LWA)	92 dB(A)
SOUND PRESSURE LEVEL (LPA)	81 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	3,5 m/s <sup>2</sup>
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	1,3 kg
PRODUCT DIMENSIONS (L X W X H):	153 x 123 x 153 mm
EAN	88381092715
NO LOAD SPEED	12 000 min <sup>-1</sup>
SANDING PAD DIAMETER 2	123 mm
SANDING DISC DIAMETER	125 mm
SANDING ORBIT DIAMETER	2,8 mm
PAPER DUST BAG	Yes
ABRASIVE PAPER	Yes

### USER BENEFITS

- Dust extraction through the base plate or external extraction can be connected
- Ergonomically designed handle fits your hand perfectly to provide maximum comfort and control
- Robust ball bearings with a long service life

Link to Product page - <https://makitauae.com/product/bo5030-random-orbit-sander/>