



Random Orbit Sander

BO6050J

750 W • 150 mm

■ TECHNICAL

Efficient tool with reliable rotation under load

A sander with random orbit and random orbit with forced rotation actions for a wide range of applications. Through-the-pad dust collection. Pad diameter of 150 mm. Comes in a Makpac case.

SPECIFICATIONS

MAXIMUM OUTPUT POWER	750 W
POWER SUPPLY CORD	2,5 m
■ SOUND POWER LEVEL (LWA)	93 dB(A)
SOUND PRESSURE LEVEL (LPA)	82 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	5,0 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	2,6 kg
PRODUCT DIMENSIONS (L X W X H):	330 x 155 x 145 mm
EAN	88381804592
ORBITS PER MINUTE	1600 - 6800 min ⁻¹
SANDING PAD DIAMETER 2	150 mm
SANDING DISC DIAMETER	150 mm
SANDING ORBIT DIAMETER	5,5 mm

USER BENEFITS

- 2 settings for polishing and polishing
- fits perfectly as a polish machine
- The rubber coating on the handle ensures a firm working grip

Link to Product page - <https://makitauae.com/product/bo6050j-random-orbit-sander/>