



Combination Hammer

HR2600



Product Description

800 W • SDS-Plus • 26 mm • 2,9 J

Professional two-mode rotary hammer

Efficient combination hammer compatible with SDS-Plus bits. Suitable for impact and unstressed drilling. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min-1 from a switch. Impact energy of 2,9 J and optimal drilling range of 8 - 18 mm in concrete. Max. drilling capacity of 26 mm in concrete.

Product Features

- Variable speed
- Double insulated
- Ergonomic handle
- 360° swivel side handle
- 2-mode operation for "Rotation Only" or "Hammering with Rotation"

Barcode

88381606561

Product Specifications

Vibration Level (3 axes), Drilling	= 2,5 m/s ²
Drilling diameter with TCT core bit	68 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	15,4 m/s ²
Optimum Drilling Diameter Range in Concrete	8.0-18 mm
Sound Pressure Level	90 dB(A)
Power Supply Cord	2,5 m
Impact Energy	2,4 J
Continuous Input Power	800 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Product Dimensions (L x W x H):	361 x 77 x 209 mm
Impacts per Minute (IPM)	0 - 4600 min ⁻¹
Sound Power Level (LWA)	101 dB(A)
Weight Without Cable (EPTA)	3,0 kg
Noise Uncertainty (K Factor)	3 dB(A)

Max. Drilling Diameter in Concrete	26 mm
Adapted for SDS-PLUS bits	1
Tool Category	Hammer Drilling and Chiseling
No load speed	0 - 1200 min ⁻¹

More info

<https://makitauae.com/product/combination-hammer-hr2600/>