



Combination Hammer

HR2631FT



Product Description

800 W • SDS-Plus • 26 mm • 2,9 J
Three-mode, anti-vibration rotary hammer with quick-change chuck
An efficient combination hammer with AVT anti-vibration system for SDS-Plus bits. Suitable for impact and unstressed drilling and chipping. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min-1 from a switch. Impact energy of 2,9 J and optimal drilling range of 8 - 18 mm in concrete, with a max. capacity of 26 mm.

Product Features

- LED light illuminates the work site
- With SDS-PLUS quick-change chuck
- Includes Makita basecap and SDS-Drill range

Barcode

88381687218

Product Specifications

Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²
Drilling diameter with TCT core bit	68 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	11,6 m/s ²
Sound Pressure Level	91 dB(A)
Power Supply Cord	2,5 m
Impact Energy	2,4 J
Continuous Input Power	800 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration: Chiselling	9,8 m/s ²
Product Dimensions (L x W x H):	385 x 77 x 209 mm
Impacts per Minute (IPM)	0 - 4600 min ⁻¹
Sound Power Level (LWA)	102 dB(A)
Weight Without Cable (EPTA)	3,1 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	26 mm
Adapted for SDS-PLUS bits	1

Tool Category	Hammer Drilling and Chiseling
No load speed	0 - 1 200 min ⁻¹

More info

<https://makitauae.com/product/combination-hammer-hr2631ft/>