



Combination Hammer

HR2661



Product Description

800 W • SDS-Plus • 26 mm • 2,9 J
Three-mode, anti-vibration rotary hammer with dust bag and quick-change chuck for professional use
A robust combination hammer for SDS-Plus bits with an AVT anti-vibration system and HEPA self dust collection. Suitable for impact and unstressed drilling and chipping. 800 W output and speed can be adjusted between 0 and 1 200 min-1 from a switch. Impact energy of 2,9J and optimal drilling range of 8 – 18 mm in concrete, with a max. capacity of 26 mm.

Product Features

- HEPA filter removes particles with an efficiency rating of 99.75%
- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- Rear handle with soft rubber grip, ergonomically designed for comfortable operation
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- Variable speed trigger allows operator to adjust speed based on materials or application
- Double insulated
- Depth gauge for increased drilling consistency

Barcode

88381845991

Product Specifications

Plastic Carrying Case	1
Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²
Drilling diameter with TCT core bit	68 - 80 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	9,3 m/s ²
Optimum Drilling Diameter Range in Concrete	8.0-18 mm
Sound Pressure Level	90 dB(A)
Power Supply Cord	2,5 m
Impact Energy	2,2 J
Continuous Input Power	800 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Vibration: Chiselling	7,0 m/s ²
Product Dimensions (L x W x H):	666 x 89 x 228 mm
Impacts per Minute (IPM)	0 - 4500 min ⁻¹

Sound Power Level (LWA)	101 dB(A)
Weight Without Cable (EPTA)	3,3 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Drilling Diameter in Concrete	26 mm
Adapted for SDS-PLUS bits	1
Tool Category	Hammer Drilling and Chiseling
No load speed	0 - 1100 min ⁻¹

More info

<https://makitauae.com/product/combination-hammer-hr2661/>