

Combination Hammer LXT

DHR263Z



Product Description

36V (18Vx2) LXT • SDS-PLUS • 26 mm • 3,0 J

Professional brushless, three-mode combination hammer

An efficient rotary hammer with anti-vibration rear and side handles, accepts SDS-Plus bits. Two 18V LXT batteries achieve a high voltage of 18V+18V. Suited to impact and unstressed drilling and chipping. Speed range of 0 - 1 200 min⁻¹. Impact energy of 3,0 J and max. drilling capacity of 26 mm in concrete. Tool only, battery and charger not included.

Product Features

- LED light illuminates the work site
- Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381663618

Product Specifications

Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	32 mm
Vibration Level (3 axes), Impact Drilling	17,6 m/s ²
Optimum Drilling Diameter Range in Concrete	6,0-16 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Drilling diameter with TCT core bit	54 mm
Tool weight with battery (EPTA)	3,5 - 4,7 kg
Battery Voltage	2 x 18 V
Sound Pressure Level	94 dB(A)
Product Dimensions (L x W x H):	350 x 116 x 232 mm
Vibration: Chiselling	14,3 m/s ²
Impacts per Minute (IPM)	0 - 5000 min ⁻¹
Sound Power Level (LWA)	102 dB(A)
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	3,3 kg
Impact Energy	2,5 J
Vibration Uncertainty (K Factor)	1,8 m/s ²
Noise Uncertainty (K Factor)	3 dB(A)

Tool Category	Hammer Drilling and Chiseling
Adapted for SDS-PLUS bits	1
Max. Drilling Diameter in Concrete	26 mm
No load speed	0 - 1250 min ⁻¹

Standard Equipment

- Sold without Battery or Charger

More info

<https://makitauae.com/product/combination-hammer-lxt-dhr263z/>