



# Combination Hammer XGT

## HR002GM201



### Product Description

40V MAX XGT • SDS-PLUS • 28 mm • 3,2 J  
**Three-mode, anti-vibration combination hammer with remote dust extraction start for professionals**  
Efficient combination hammer HR002G delivers high power for professional work. The tool is lightweight and the tool balance is redesigned for increased operability. HR002G is equipped with Anti vibration technology (AVT), Active Feedback Technology (AFT) and Auto-start Wireless System (AWS). Two 4.0 Ah batteries, rapid charger and wireless unit in a Makpac case.

### Product Features

- Quick-release chuck for metal and wood drill bits without impact.
- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- Auto-start Wireless System (AWS) connects to vacuum cleaner with Bluetooth
- Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- Low power consumption thanks to brushless motor
- Impact drilling, non-impact drilling and spike function
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- Battery protection circuit protects against overloading, over-discharging and over-heating

### Barcode

88381892841

### Product Specifications

|                                             |                       |
|---------------------------------------------|-----------------------|
| Vibration Level (3 axes), Drilling          | 2,5 m/s <sup>2</sup>  |
| Drilling diameter with TCT core bit         | 54 mm                 |
| Tool weight with battery (EPTA)             | 4,1 - 5,5 kg          |
| Max. Drilling Diameter in Steel             | 13 mm                 |
| Max. Drilling Diameter in Wood              | 32 mm                 |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)  | Li-ion                |
| Vibration Level (3 axes), Impact Drilling   | 15,6 m/s <sup>2</sup> |
| Optimum Drilling Diameter Range in Concrete | 10.0-18 mm            |
| Battery Voltage                             | 40 V                  |
| Brushless Motor                             | YES                   |
| Sound Pressure Level                        | 93 dB(A)              |

|                                           |                               |
|-------------------------------------------|-------------------------------|
| <b>Impact Energy</b>                      | 2,9 J                         |
| <b>Vibration Uncertainty (K Factor)</b>   | 2,4 m/s <sup>2</sup>          |
| <b>Vibration: Chiselling</b>              | 11,4 m/s <sup>2</sup>         |
| <b>Product Dimensions (L x W x H):</b>    | 404 x 102 x 238 mm            |
| <b>Impacts per Minute (IPM)</b>           | 0 - 5000 min <sup>-1</sup>    |
| <b>System</b>                             | XGT 40Vmax/80V max            |
| <b>Sound Power Level (LWA)</b>            | 104 dB(A)                     |
| <b>Product net weight (new)</b>           | 3,1 kg                        |
| <b>Voltage XGT</b>                        | 1                             |
| <b>Noise Uncertainty (K Factor)</b>       | 3 dB(A)                       |
| <b>Max. Drilling Diameter in Concrete</b> | 28 mm                         |
| <b>Adapted for SDS-PLUS bits</b>          | 1                             |
| <b>Tool Category</b>                      | Hammer Drilling and Chiseling |
| <b>Electronic brake</b>                   | 1                             |
| <b>AWS FUNCTION</b>                       | YES                           |
| <b>No load speed</b>                      | 0 - 980 min <sup>-1</sup>     |

## Standard Equipment

- 1pc DC40RA Fast Charger
- 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- Makpack Case

## More info

<https://makitauae.com/product/combination-hammer-xgt-hr002gm201/>