



Angle Grinder LXT®

DGA519Z

18V • 125 mm • 3 000 – 8 500 min?¹

product image type unknown

■ TECHNICAL

The X-LOCK mechanism allows the installation / removal of X-LOCK discs without the need for a tool.

With X-Lock, one click is all you need. Insert the wheel into the X-Lock bracket and press it into place. To replace the wheel, simply pull the lever and remove wheel . The X-Lock allows you to change wheels quickly and easily - without the need for a key and even when wearing gloves. Tool only, battery and charger not included.

SPECIFICATIONS

SOUND PRESSURE LEVEL (LPA)	80 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
■ VIBRATION LEVEL (3 AXES)	5,5 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
PRODUCT DIMENSIONS (L X W X H):	382 x 140 x 147 mm
EAN	88381893510
NO LOAD SPEED	3000 - 8500 min? ¹
BRUSHLESS MOTOR	Yes
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	2,7 - 3 kg
NOMINAL BATTERY VOLTAGE	18 V
BORE SIZE (ARBOR DIAMETER)	22,23 mm
SPINDLE THREAD	M14
VOLTAGE LXT	Yes
GRINDING DISC DIAMETER	125 mm
DEAD MAN'S SWITCH (NO LOCK-ON)	Yes
GRINDING WHEEL	Yes
MAX. DEPTH OF CUT	29 mm
ANTI-RESTART FUNCTION (NVR SWITCH)	Yes
ELECTRONIC BRAKE	Yes
GRIP AVT	Yes
AWS FUNCTION	Yes

USER BENEFITS

- Body model - delivered without battery and charger.
- Brushless maintenance-free and long-life motor
- disc brake
- Paddle switch

Link to Product page - <https://makitauae.com/product/dga519z-angle-grinder-lxt/>