



Angle Grinder LXT®

DGA701ZKU

18V+18V • 180 mm • 7 800 min?¹

Efficient brushless tool with brake and safety switch underneath for high-capacity applications

An efficient, high-capacity brushless angle grinder with a 180 mm wheel for demanding professional use. A high 18V+18V voltage is achieved with two 18V LXT batteries. Constant speed electronics, overload protection and wheel brake for added safety. Equipped with a safety switch underneath. Tool only, battery and charger not included.



TECHNICAL

SPECIFICATIONS

| | |
|------------------------------------|------------------------|
| SOUND PRESSURE LEVEL (LPA) | 88 dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 3 dB(A) |
| VIBRATION LEVEL (3 AXES) | 7,5 m/s ² |
| VIBRATION UNCERTAINTY (K FACTOR) | 1,5 m/s ² |
| PRODUCT WEIGHT | 5,0 - 6,0 kg |
| PRODUCT DIMENSIONS (L X W X H): | 499 x 200 x 158 mm |
| NO LOAD SPEED | 7800 min? ¹ |
| BRUSHLESS MOTOR | Yes |
| BATTERY PROTECTION | Yes |
| TOOL WEIGHT WITH BATTERY (EPTA) | 6,0 kg |
| NOMINAL BATTERY VOLTAGE | 2 x 18 V |
| BORE SIZE (ARBOR DIAMETER) | 22,23 mm |
| SPINDLE THREAD | M14 |
| VOLTAGE LXT | Yes |
| AVERAGE CHARGING TIME | 90 min |
| GRINDING DISC DIAMETER | 180 mm |
| DEAD MAN'S SWITCH (NO LOCK-ON) | Yes |
| GRINDING WHEEL | Yes |
| MAX. DEPTH OF CUT | 41 mm |
| ANTI-RESTART FUNCTION (NVR SWITCH) | Yes |
| ELECTRONIC BRAKE | Yes |
| GRIP AVT | Yes |

USER BENEFITS

- Battery protection system automatically shuts off power when the battery level is low
- Brushless maintenance-free and long-life motor

Link to Product page - <https://makitauae.com/product/dga701zku-angle-grinder-lxt/>