

Hammer Drill Driver LXT®

DHP453RFE

18V • 42 Nm • 0 − 1 300 min?¹

Combi drill with hammer action for demanding amateur builders

For screwdriving and drilling with or without hammer action, two power settings. Max. torque of 42 / 27 Nm. Suitable for light professional use or demanding amateur use. Includes 2 x 3,0 Ah batteries and a charger in a case.



TECHNICAL

SPECIFICATIONS

IMPACT
SOUND POWER LEVEL (LWA)
SOUND PRESSURE LEVEL (LPA)
NOISE UNCERTAINTY (K FACTOR)
VIBRATION UNCERTAINTY (K FACTOR)
PRODUCT DIMENSIONS (L X W X H):

EAN

NO LOAD SPEED

MAX. DRILLING DIAMETER IN WOOD MAX. DRILLING DIAMETER IN CONCRETE MAX. DRILLING DIAMETER IN STEEL

DRILL CHUCK CAPACITY

VIBRATION LEVEL (3 AXES), IMPACT DRILLING

BRUSHLESS MOTOR BATTERY PROTECTION

TOOL WEIGHT WITH BATTERY (EPTA)

NOMINAL BATTERY VOLTAGE

MAX. FASTENING TORQUE HARD/SOFT

VOLTAGE LXT

VIBRATION LEVEL (3 AXES), DRILLING

CLUTCH TORQUE SETTING

BATTERY CHEMISTRY (NI-CD / NI-MH / LI-ION)

DRIVING SHANK

MAX. DRILLING DIAMETER IN MASONRY

CAPACITY STANDARD SCREW

0 - 6000 / 19 500 min?1

94 dB(A) 83 dB(A) 3 dB(A) 1.5 m/s²

239 x 79 x 227 mm 88381661249

0 - 400 / 1300 min?¹

36 mm 13 mm 13 mm 1,5 - 13 mm 10,0 m/s² Yes Yes 1,7 - 2,0 kg 18 V 42 / 27 Nm Yes ? 2,5 m/s²

16 Li-ion 1/2"-20UN

1/2"-20UNF " 13 mm 187 kpl

USER BENEFITS

The rubber coating on the handle ensures a firm working grip

Link to Product page - https://makitauae.com/product/dhp453rfe-hammer-drill-driver-lxt/