



Combination Hammer LXT®

DHR202RFJ

18V • SDS-Plus • 20 mm • 1,9 J

Professional three-mode combination hammer

An efficient combination hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 1100 min⁻¹. Impact energy of 1,9 J and max. drilling capacity of 20 mm in concrete. Includes 2 x 3,0 Ah batteries and a charger in a Makpac case.

product image type unknown

TECHNICAL

SPECIFICATIONS

IMPACT	0 - 4000 min ⁻¹
IMPACT ENERGY	1,9 J
SOUND POWER LEVEL (LWA)	98 dB(A)
SOUND PRESSURE LEVEL (LPA)	87 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION: CHISELLING	11 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
PRODUCT DIMENSIONS (L X W X H):	358 x 84 x 259 mm
NO LOAD SPEED	0 - 1100 min ⁻¹
MAX. DRILLING DIAMETER IN WOOD	26 mm
MAX. DRILLING DIAMETER IN CONCRETE	20 mm
MAX. DRILLING DIAMETER IN STEEL	13 mm
SIDE GRIP	Yes
VIBRATION LEVEL (3 AXES), IMPACT DRILLING	14,5 m/s ²
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	3,2 – 4,0 kg
NOMINAL BATTERY VOLTAGE	18 V
VOLTAGE LXT	Yes
VIBRATION LEVEL (3 AXES), DRILLING	3 m/s ²
OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE	6 - 10 mm

USER BENEFITS

- Battery protection system automatically shuts off power when the battery level is low
- Body model - delivered without battery and charger.
- LED light illuminates the work site

Link to Product page - <https://makitauae.com/product/dhr202rfj-combination-hammer-lxt/>