



Combination Hammer LXT®

DHR242Z

18V • SDS-Plus • 24 mm • 2,0 J

Professional brushless, three-mode combination hammer

An efficient combination hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min⁻¹. Impact energy of 2,0 J and max. drilling capacity of 24 mm in concrete. Tool only, battery and charger not included.



TECHNICAL

SPECIFICATIONS

IMPACT	0 - 4700 min ¹
IMPACT ENERGY	2,0 J
SOUND POWER LEVEL (LWA)	101 dB(A)
SOUND PRESSURE LEVEL (LPA)	90 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION: CHISELLING	10,5 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
PRODUCT DIMENSIONS (L X W X H):	328 x 85 x 213 mm
NO LOAD SPEED	0 - 950 min ¹
MAX. DRILLING DIAMETER IN WOOD	27 mm
MAX. DRILLING DIAMETER IN CONCRETE	24 mm
MAX. DRILLING DIAMETER IN STEEL	13 mm
SIDE GRIP	Yes
VIBRATION LEVEL (3 AXES), IMPACT DRILLING	13,5 m/s ²
BRUSHLESS MOTOR	Yes
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	3,1 - 4,8 kg
NOMINAL BATTERY VOLTAGE	18 V
VOLTAGE LXT	Yes
VIBRATION LEVEL (3 AXES), DRILLING	3,5 m/s ²
OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE	6 - 12 mm

USER BENEFITS

- Body model - delivered without battery and charger.
- Brushless maintenance-free and long-life motor

Link to Product page - <https://makitauae.com/product/dhr242z-combination-hammer-lxt/>