



# Combination Hammer LXT®

## DHR263Z

18V+18V • SDS-Plus • 26 mm • 3,0 J

### Professional brushless, three-mode combination hammer

An efficient rotary hammer with anti-vibration rear and side handles, accepts SDS-Plus bits. Two 18V LXT batteries achieve a high voltage of 18V+18V. Suited to impact and unstressed drilling and chipping. Speed range of 0 – 1 200 min<sup>-1</sup>. Impact energy of 3,0 J and max. drilling capacity of 26 mm in concrete. Tool only, battery and charger not included.



### TECHNICAL

## SPECIFICATIONS

IMPACT	0 - 5000 min <sup>-1</sup>
IMPACT ENERGY	2,5 J
SOUND POWER LEVEL (LWA)	102 dB(A)
SOUND PRESSURE LEVEL (LPA)	94 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION: CHISELLING	14 m/s <sup>2</sup>
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
PRODUCT DIMENSIONS (L X W X H):	350 x 116 x 232 mm
NO LOAD SPEED	0 - 1250 min <sup>-1</sup>
MAX. DRILLING DIAMETER IN WOOD	32 mm
MAX. DRILLING DIAMETER IN CONCRETE	26 mm
MAX. DRILLING DIAMETER IN STEEL	13 mm
SIDE GRIP	Yes
VIBRATION LEVEL (3 AXES), IMPACT DRILLING	14,5 m/s <sup>2</sup>
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	3,5 - 4,7 kg
NOMINAL BATTERY VOLTAGE	2 x 18 V
VOLTAGE LXT	Yes
VIBRATION LEVEL (3 AXES), DRILLING	3,0 m/s <sup>2</sup>
OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE	6 - 16 mm
DRILLING DIAMETER WITH TCT CORE BIT	54 mm

## USER BENEFITS

- LED light illuminates the work site

Link to Product page - <https://makitauae.com/product/dhr263z-combination-hammer-lxt/>