

## Combination Hammer LXT® DHR281ZJ 18V+18V • SDS-Plus • 28 mm • 3,2 J

## Brushless, three-mode, anti-vibration combination hammer with quick change chuck for professionals

A robust tool for SDS-Plus bits with AVT (anti-vibration technology) and a quick change chuck. Two 18V LXT batteries achieve a high voltage of 18V+18V. Suited to impact and unstressed drilling and chipping. Speed range of 0 – 980 min-1. Impact energy of 3,2 J, max. drilling capacity of 28 mm in concrete. Tool in Makpac case, battery and charger not included.

## **SPECIFICATIONS**

NOMINAL BATTERY VOLTAGE
VOLTAGE LXT
BATTERY PROTECTION
BRUSHLESS MOTOR
IMPACT ENERGY
OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE
MAX. DRILLING DIAMETER IN CONCRETE
MAX. DRILLING DIAMETER IN WOOD
MAX. DRILLING DIAMETER IN STEEL
IMPACT
NO LOAD SPEED
SIDE GRIP
SOUND POWER LEVEL (LWA)
SOUND PRESSURE LEVEL (LPA)
NOISE UNCERTAINTY (K FACTOR)
VIBRATION LEVEL (3 AXES), DRILLING
VIBRATION LEVEL (3 AXES), IMPACT DRILLING
VIBRATION: CHISELLING
VIBRATION UNCERTAINTY (K FACTOR)
PRODUCT DIMENSIONS (L X W X H):
DRILLING DIAMETER WITH TCT CORE BIT
TOOL WEIGHT WITH BATTERY (EPTA)
EAN

**USER BENEFITS** 

- Body model delivered without battery and charger.
- Brushless maintenance-free and long-life motor
- LED light illuminates the work site

Link to Product page - https://makitauae.com/product/dhr281zj-combination-hammer-lxt/

productoingr type unknown

## **TECHNICAL**

2 x 18 V Yes Yes Yes 2,9 J 10 - 18 mm 28 mm 32 mm 13 mm 0 - 5000 min?1 0 - 980 min?<sup>1</sup> Yes 103 dB(A) 92 dB(A) 3 dB(A) 2.5 m/s<sup>2</sup> 9,5 m/s<sup>2</sup> 9,0 m/s<sup>2</sup> 1,5 m/s<sup>2</sup> 404 x 134 x 232 mm 54 mm 3,1 - 6,3 kg 88381858014