



Combination Hammer LXT®

DHR283ZJ

18V+18V • SDS-Plus • 28 mm • 3,2 J

Brushless, three-mode, anti-vibration combination hammer with quick change chuck for professionals and with AWS function

An efficient tool with AVT (anti-vibration technology), remote dust extraction start and a quick change chuck, accepts SDS-Plus bits. Two 18V LXT batteries provide a high voltage of 18V+18V. For impact and unstressed drilling and chipping. Impact energy of 3,2 J, max. capacity of 28 mm in concrete. Tool in Makpac case, battery and charger not included.



TECHNICAL

SPECIFICATIONS

| | |
|---|----------------------------|
| NOMINAL BATTERY VOLTAGE | 2 x 18 V |
| VOLTAGE LXT | Yes |
| BATTERY PROTECTION | Yes |
| BRUSHLESS MOTOR | Yes |
| IMPACT ENERGY | 2,9 J |
| OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE | 10 - 18 mm |
| MAX. DRILLING DIAMETER IN CONCRETE | 28 mm |
| MAX. DRILLING DIAMETER IN WOOD | 32 mm |
| MAX. DRILLING DIAMETER IN STEEL | 13 mm |
| IMPACT | 0 - 5000 min? ¹ |
| NO LOAD SPEED | 0 - 980 min? ¹ |
| PLASTIC CARRYING CASE | Yes |
| SIDE GRIP | Yes |
| SOUND POWER LEVEL (LWA) | 103 dB(A) |
| SOUND PRESSURE LEVEL (LPA) | 92 dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 3 dB(A) |
| VIBRATION LEVEL (3 AXES), DRILLING | 2,5 m/s ² |
| VIBRATION LEVEL (3 AXES), IMPACT DRILLING | 9,5 m/s ² |
| VIBRATION: CHISELLING | 8,5 m/s ² |
| VIBRATION UNCERTAINTY (K FACTOR) | 1,5 m/s ² |
| PRODUCT DIMENSIONS (L X W X H): | 404 x 134 x 232 mm |
| DRILLING DIAMETER WITH TCT CORE BIT | 54 mm |
| AWS READY | Yes |
| TOOL WEIGHT WITH BATTERY (EPTA) | 3,1 - 6,4 kg |
| EAN | 88381857888 |

USER BENEFITS

- Brushless maintenance-free and long-life motor
- LED light illuminates the work site

Link to Product page - <https://makitauae.com/product/dhr283zj-combination-hammer-lxt/>