



Reciprocating Saw LXT®

DJR185Z

18V • 0 – 3 300 min⁻¹ • 13 mm

Compact reciprocating saw for light use, also accepts jigsaw bits

A straight-framed light and small reciprocating saw offers access to tight places. Two separate switches enable diverse working postures. Stroke length of 13 mm, stroke rate can be adjusted between 0 – 3 300 min⁻¹ from a switch. LED light. Tool only, battery and charger not included.



TECHNICAL

SPECIFICATIONS

IMPACT	0 - 3000 min ⁻¹
SOUND PRESSURE LEVEL (LPA)	76 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	8,0 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
PRODUCT DIMENSIONS (L X W X H):	392 x 81 x 209 mm
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	1,5 - 1,8 kg
NOMINAL BATTERY VOLTAGE	18 V
LENGTH OF STROKE	13 mm
MAX. CUTTING CAPACITY IN WOOD (90°)	50 mm
MAX. CUTTING CAPACITY IN STEEL PIPE	50 mm
VOLTAGE LXT	Yes

USER BENEFITS

- Battery protection system automatically shuts off power when the battery level is low
- Body model - delivered without battery and charger.
- LED light illuminates the work site

Link to Product page - <https://makitauae.com/product/djr185z-reciprocating-saw-lxt/>