



Reciprocating Saw LXT®

DJR185Z

18V • 0 – 3 300 min⁻¹ • 13 mm

Compact reciprocating saw for light use, also accepts jigsaw bits

A straight-framed light and small reciprocating saw offers access to tight places. Two separate switches enable diverse working postures. Stroke length of 13 mm, stroke rate can be adjusted between 0 – 3 300 min⁻¹ from a switch. LED light. Tool only, battery and charger not included.



TECHNICAL

SPECIFICATIONS

| | |
|-------------------------------------|----------------------------|
| IMPACT | 0 - 3000 min ⁻¹ |
| SOUND PRESSURE LEVEL (LPA) | 76 dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 3 dB(A) |
| VIBRATION LEVEL (3 AXES) | 8,0 m/s ² |
| VIBRATION UNCERTAINTY (K FACTOR) | 1,5 m/s ² |
| PRODUCT DIMENSIONS (L X W X H): | 392 x 81 x 209 mm |
| BATTERY PROTECTION | Yes |
| TOOL WEIGHT WITH BATTERY (EPTA) | 1,5 - 1,8 kg |
| NOMINAL BATTERY VOLTAGE | 18 V |
| LENGTH OF STROKE | 13 mm |
| MAX. CUTTING CAPACITY IN WOOD (90°) | 50 mm |
| MAX. CUTTING CAPACITY IN STEEL PIPE | 50 mm |
| VOLTAGE LXT | Yes |

USER BENEFITS

- Battery protection system automatically shuts off power when the battery level is low
- Body model - delivered without battery and charger.
- LED light illuminates the work site

Link to Product page - <https://makitauae.com/product/djr185z-reciprocating-saw-lxt/>