



Cordless Reciprocating Saw LXT®

DJR189

18V • 0 – 3100 min⁻¹ • 22 mm

Powerful machine in Lightweight / compact design

The compact design allows you to work in tight spaces. The new design and arrangement of the handle makes it possible to transfer the force to the work material even when operating with one hand. With powerful, brushless motor and counterweight to reduce vibrations. Tool-free saw blade change and LED work light.



TECHNICAL

SPECIFICATIONS

| | |
|---|----------------------------|
| Nominal Battery Voltage | 18 V |
| Voltage LXT | Yes |
| Brushless Motor | Yes |
| Strokes per Minute (SPM) | 0 - 3100 min ⁻¹ |
| Length of Stroke | 22 mm |
| Max. Cutting Capacity in Wood (90°) | 255 mm |
| Max. Cutting Capacity in Steel Pipe | 130 mm |
| Sound Power Level (LWA) | 99 dB(A) |
| Sound Pressure Level (LpA) | 88 dB(A) |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Vibration Uncertainty (K Factor) | 1.5 m/s ² |
| Tool weight with battery (EPTA) | 2.2 - 2.5 kg |
| Product Dimensions (L x W x H): | 410 x 81 x 182 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Vibration Level (3 axes), Cutting Chipboard | 9.0 m/s ² |
| Vibration Level (3 axes), Cutting Wood | 8.7 m/s ² |
| Product net weight | 1.9 kg |

USER BENEFITS

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low
- Brushless motor is electronically controlled to optimise battery energy use for longer run time per charge

Link to Product page - <https://makitauae.com/product/djr189-reciprocating-saw-lxt/>