

# **Reciprocating Saw LXT®**

## **DJR360Z**

 $18V+18V \cdot 0 - 3000 \text{ min}?^{1} \cdot 32 \text{ mm}$ 

#### Extremely efficient brushless reciprocating saw

An efficient brushless saw for spark-free cutting of metal and demolition work. Two 18V LXT batteries achieve a voltage of 18V+18V. Two speeds, stroke length of 32 mm and stroke rate of  $0-2\,800$  min-1 with continuous control from the switch. Quick-release blade attachment. Tool only, battery and charger not included.



**TECHNICAL** 

### **SPECIFICATIONS**

IMPACT
SOUND POWER LEVEL (LWA)

SOUND PRESSURE LEVEL (LPA)
NOISE UNCERTAINTY (K FACTOR)
VIBRATION LEVEL (3 AXES)
VIBRATION UNCERTAINTY (K FACTOR)
PRODUCT DIMENSIONS (L X W X H):
BRUSHLESS MOTOR
BATTERY PROTECTION
TOOL WEIGHT WITH BATTERY (EPTA)
NOMINAL BATTERY VOLTAGE
LENGTH OF STROKE
MAX. CUTTING CAPACITY IN WOOD (90°)
MAX. CUTTING CAPACITY IN STEEL PIPE

96 dB(A) 85 dB(A) 3 dB(A) 16,5 m/s<sup>2</sup> 1,5 m/s<sup>2</sup> 449 x 116 x 243 mm Yes Yes 4,0 - 4,7 kg 2 x 18 V 32 mm 255 mm 130 mm Yes

0 - 2300 / 3000 min?1

#### **USER BENEFITS**

**VOLTAGE LXT** 

- Battery protection system automatically shuts off power when the battery level is low
- Body model delivered without battery and charger.
- LED light illuminates the work site

Link to Product page - https://makitauae.com/product/djr360z-reciprocating-saw-lxt/