



Reciprocating Saw LXT®

DJR360Z

18V+18V • 0 – 3 000 min⁻¹ • 32 mm

Extremely efficient brushless reciprocating saw

An efficient brushless saw for spark-free cutting of metal and demolition work. Two 18V LXT batteries achieve a voltage of 18V+18V. Two speeds, stroke length of 32 mm and stroke rate of 0 – 2 800 min⁻¹ with continuous control from the switch. Quick-release blade attachment. Tool only, battery and charger not included.



TECHNICAL

SPECIFICATIONS

IMPACT	0 - 2300 / 3000 min ⁻¹
SOUND POWER LEVEL (LWA)	96 dB(A)
SOUND PRESSURE LEVEL (LPA)	85 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	16,5 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
PRODUCT DIMENSIONS (L X W X H):	449 x 116 x 243 mm
BRUSHLESS MOTOR	Yes
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	4,0 - 4,7 kg
NOMINAL BATTERY VOLTAGE	2 x 18 V
LENGTH OF STROKE	32 mm
MAX. CUTTING CAPACITY IN WOOD (90°)	255 mm
MAX. CUTTING CAPACITY IN STEEL PIPE	130 mm
VOLTAGE LXT	Yes

USER BENEFITS

- Battery protection system automatically shuts off power when the battery level is low
- Body model - delivered without battery and charger.
- LED light illuminates the work site

Link to Product page - <https://makitauae.com/product/djr360z-reciprocating-saw-lxt/>