



## Slide Compound Saw LXT®

### DLS713Z

18V • 190 mm • 2 200 min-1

#### A light and powerful slide compound saw for builders

A cordless slide compound saw for cross and mitre cutting with a blade diameter of 190 mm. An ideal choice for construction and other demanding sectors. Four steel poles with four linear ball bearings ensure stable and accurate cutting. Tool only, battery and charger not included.



#### TECHNICAL

### SPECIFICATIONS

SOUND POWER LEVEL (LWA)	98 dB(A)
SOUND PRESSURE LEVEL (LPA)	88 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	? 2,5 m/s <sup>2</sup>
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
PRODUCT DIMENSIONS (L X W X H):	655 x 430 x 454 mm
NO LOAD SPEED	2200 min <sup>-1</sup>
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	12,4 - 12,7 kg
NOMINAL BATTERY VOLTAGE	18 V
BLADE DIAMETER	190 mm
BORE SIZE (ARBOR DIAMETER)	20 mm
MAX. BEVEL RANGE (LEFT)	45 / 5 °
VOLTAGE LXT	Yes
CAPACITY 90°	52 x 300 mm
CAPACITY 45°	52 x 212 mm
BLADE	190 x 20 mm
CAPACITY 45° LEFT	40 x 300 mm
MAX. MITRE RANGE (LEFT)	47 / 57 °

### USER BENEFITS

- Battery protection system automatically shuts off power when the battery level is low
- Body model - delivered without battery and charger.

Link to Product page - <https://makitauae.com/product/dls713z-slide-compound-saw-lxt/>