

## DPO600RTE

LXT® • 18V • 780 min<sup>?1</sup> • 150 mm

### Random Orbit Polisher LXT® for professionals

Normal mode is orbital action with forced rotation of the pad for rough polishing such as surface treatment. Finishing mode is orbital action with free rotation of the pad for fine polishing; allows 30 min. operation with 18V 6.0 Ah Li-ion battery. Damage guards for car body. Includes 2 x 5,0 Ah batteries and a charger.



## TECHNICAL

### SPECIFICATIONS

IMPACT	0 - 13 600 min <sup>?1</sup>
SOUND POWER LEVEL (LWA)	94 dB(A)
SOUND PRESSURE LEVEL (LPA)	83 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
PRODUCT DIMENSIONS (L X W X H):	530 x 148 x 126 mm
NO LOAD SPEED	0 - 780 min <sup>?1</sup>
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	3,1 - 3,6 kg
NOMINAL BATTERY VOLTAGE	18 V
ORBITS PER MINUTE	0 - 6800 min <sup>?1</sup>
VOLTAGE LXT	Yes
VIBRATIONS PER MINUTE	0 - 13 600 min <sup>?1</sup>
SANDING DISC DIAMETER	150 mm
SANDING ORBIT DIAMETER	5,5 mm
VIBRATION LEVEL (3 AXES), POLISHING	10,0 m/s <sup>2</sup>

### USER BENEFITS

Link to Product page - <https://makitauae.com/product/dpo600rte/>