



Angle Grinder XGT®

GA013GZ

40V max • 125 mm • 8 500 min?¹

Efficient brushless tool with paddle switch for cutting and grinding

A compact, brushless angle grinder with paddle switch and 125 mm blade diameter for demanding professional use. The machine features standard electronics, electronic brake, overload protection and AFT-active feedback detection technology. Tool only, battery and charger not included.



TECHNICAL

SPECIFICATIONS

SOUND POWER LEVEL (LWA)	93 dB(A)
SOUND PRESSURE LEVEL (LPA)	82 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	6,5 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
PRODUCT WEIGHT	3,60 kg
PRODUCT DIMENSIONS (L X W X H):	410 x 140 x 168 mm
EAN	88381898522
NO LOAD SPEED	8500 min? ¹
GRIP	Yes
BRUSHLESS MOTOR	Yes
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	3,2 - 3,5 kg
NOMINAL BATTERY VOLTAGE	40 V
BORE SIZE (ARBOR DIAMETER)	22,23 mm
SPINDLE THREAD	M14
GRINDING DISC DIAMETER	125 mm
GRINDING WHEEL	Yes
LOCK NUT WRENCH	Yes
ANTI-RESTART FUNCTION (NVR SWITCH)	Yes
VOLTAGE XGT	Yes
ELECTRONIC BRAKE	Yes

USER BENEFITS

- Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
- Anti-restart function engineered to prevent motor start up when battery is inserted with switch locked on
- Brushless maintenance-free and long-life motor
- Electric brake for maximum productivity and increased operator safety
- Outperforming performance and efficiency similar to corded 1 000 W class grinder
- Paddle switch; Easy-to-hold slim grip achieved by optimized parts allocation
- Side grip can be installed on either side of the tool
- Slim body design for a good grip.
- Soft start suppresses start-up reaction for more control and better accuracy
- Spindle lock for easy wheel changes
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions

Link to Product page - <https://makitauae.com/product/ga013gz-angle-grinder-xgt/>