



Angle Grinder XGT®

GA029GZ

40V max • 125 mm • 8 500 min?¹

Efficient brushless tool with paddle switch for cutting and grinding

A compact, brushless angle grinder with paddle switch and 125 mm blade diameter for demanding professional use. The machine features standard electronics, electronic brake, overload protection a, AFT-active feedback detection technology, AWS function and Variable Speed option. Tool only, Battery and charger not included.



TECHNICAL

SPECIFICATIONS

SOUND POWER LEVEL (LWA)	93 dB(A)
SOUND PRESSURE LEVEL (LPA)	82 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	6,0 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
PRODUCT WEIGHT	3,0 -4,5 kg
PRODUCT DIMENSIONS (L X W X H):	425 x 140 x 168 mm
EAN	88381722445
NO LOAD SPEED	3000 - 8500 min? ¹
GRIP	Yes
BRUSHLESS MOTOR	Yes
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	3,2 - 3,5 kg
NOMINAL BATTERY VOLTAGE	40 V
BORE SIZE (ARBOR DIAMETER)	22,23 mm
SPINDLE THREAD	M14
GRINDING DISC DIAMETER	125 mm
GRINDING WHEEL	Yes
LOCK NUT WRENCH	Yes
ANTI-RESTART FUNCTION (NVR SWITCH)	Yes
VOLTAGE XGT	Yes
ELECTRONIC BRAKE	Yes
AWS READY	Yes

USER BENEFITS

- Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
- Anti-restart function engineered to prevent motor start up when battery is inserted with switch locked on
- Auto-start Wireless System (AWS) connects to vacuum cleaner with Bluetooth
- Electric brake for maximum productivity and increased operator safety
- Excellent in continuous heavy-duty work
- Genuine solution for high demand industrial applications
- Outperforming performance and efficiency similar to corded 1 000 W class grinder
- Paddle switch; Easy-to-hold slim grip achieved by optimized parts allocation
- Soft start provides safety when working.
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions

Link to Product page - <https://makitauae.com/product/ga029gz-angle-grinder-xgt/>