



## Angle Grinder

### GA5034

720 W • 125 mm • 11 000 min<sup>-1</sup>

#### Compact tool for cutting and grinding

A small angle grinder for demanding applications. 720 W motor and 125 mm wheel. Labyrinth channel construction protects the armature and the field coil from impurities in the cooling air.



#### TECHNICAL

#### SPECIFICATIONS

MAXIMUM OUTPUT POWER	720 W
POWER SUPPLY CORD	2,5 m
SOUND POWER LEVEL (LWA)	97 dB(A)
SOUND PRESSURE LEVEL (LPA)	86 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	1,8 kg
PRODUCT DIMENSIONS (L X W X H):	266 x 138 x 103 mm
NO LOAD SPEED	11 000 min <sup>-1</sup>
GRIP	Yes
VIBRATION LEVEL (3 AXES), SANDING	8,0 m/s <sup>2</sup>
SPINDLE THREAD	M14
GRINDING DISC DIAMETER	125 mm
BORE (B)	22,23 mm
GRINDING WHEEL	Yes
LOCK NUT WRENCH	Yes

#### USER BENEFITS

- Additional Anchor and Field Coil Protection: Zik Zak Anchor Lacquer and Armored Field Coil.
- Extremely compact angle grinder, only 180 mm in circumference
- The labyrinth ducting of the engine compartment protects the engine from the impurities present in the cooling air.

Link to Product page - <https://makitauae.com/product/ga5034-angle-grinder/>