



## Heat gun

### ■ HG6030K

1 800 W • 250 – 500 l/min • 50 / 600 °C

#### Heat gun with 2 - temperature and 2 - speed blower settings

Heat gun with 2 - temperature and 2 - speed blower settings and cooling mode (50°C) for professional use to suit many different heating and material removal applications. Easy-to-operate slide switch for selecting right temperature. Different nozzles available as an accessory.



### TECHNICAL

## SPECIFICATIONS

MAXIMUM OUTPUT POWER	1800 W
POWER SUPPLY CORD	2,0 m
■ WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	0,57 kg
PRODUCT DIMENSIONS (L X W X H):	233 x 80 x 208 mm
EAN	88381857369
MAXIMUM FLOW RATE	250 - 500 L/min
TEMPERATURE RANGE	50 - 600 °
THERMAL SAFETY SWITCH	Yes
IEC PROTECTION CLASS	II

## USER BENEFITS

- Cooling mode for rapid cooling on nozzle change
- Easy-to-operate slide switch
- Ergonomic soft rubber grip design for comfortable operation
- With overheat protection

Link to Product page - <https://makitauae.com/product/hg6030k-heat-gun/>