



# Percussion Driver Drill XGT®

## HP001G

40V max • 140 Nm • 0 – 2 600 min?<sup>1</sup>

### ■ TECHNICAL

#### Rugged, brushless combi drill for heavy-duty screwdriving and drilling

A powerful, brushless drill for professional screwdriving and drilling with or without hammer action, two power settings. A high maximum torque of 140 / 68 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light. Two 4.0 Ah batteries and a rapid charger in a Makpac case.

### SPECIFICATIONS

|  |                                     |
|--|-------------------------------------|
| IMPACT                                     | 0 - 9750 / 39 000 min? <sup>1</sup> |
| SOUND POWER LEVEL (LWA)                    | 96 dB(A)                            |
| SOUND PRESSURE LEVEL (LPA)                 | 85 dB(A)                            |
| NOISE UNCERTAINTY (K FACTOR)               | 3 dB(A)                             |
| VIBRATION UNCERTAINTY (K FACTOR)           | 1,5 m/s <sup>2</sup>                |
| PRODUCT DIMENSIONS (L X W X H):            | 182 x 86 x 282 mm                   |
| EAN  | 88381892193                         |
| NO LOAD SPEED                              | 0 - 650 / 2600 min? <sup>1</sup>    |
| MAX. DRILLING DIAMETER IN WOOD             | 76 mm                               |
| MAX. DRILLING DIAMETER IN STEEL            | 20 mm                               |
| DRILL CHUCK CAPACITY                       | 1,5 - 13 mm                         |
| VIBRATION LEVEL (3 AXES), IMPACT DRILLING  | 6,0 m/s <sup>2</sup>                |
| BRUSHLESS MOTOR                            | Yes                                 |
| BATTERY PROTECTION                         | Yes                                 |
| TOOL WEIGHT WITH BATTERY (EPTA)            | 2,7 - 3,0 kg                        |
| NOMINAL BATTERY VOLTAGE                    | 40 V                                |
| MAX. FASTENING TORQUE HARD/SOFT            | 140 / 68 Nm                         |
| VIBRATION LEVEL (3 AXES), DRILLING         | ? 2,5 m/s <sup>2</sup>              |
| CLUTCH TORQUE SETTING                      | 41 / 21                             |
| BATTERY CHEMISTRY (NI-CD / NI-MH / LI-ION) | Li-ion                              |
| DRIVING SHANK                              | 1/2"-20UNF "                        |
| MAX. DRILLING DIAMETER IN MASONRY          | 20 mm                               |
| VOLTAGE XGT                                | Yes                                 |

### USER BENEFITS

- Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
- Battery protection system automatically shuts off power when the battery level is low
- Jog selector for easy adjustment of mounting torque, visual confirmation of the selected torque on the digital display
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions

Link to Product page - <https://makitauae.com/product/hp001g-percussion-driver-drill-xgt/>