



Combination Hammer

HR2600

800 W • SDS-Plus • 26 mm • 2,9 J

Professional two-mode rotary hammer

Efficient combination hammer compatible with SDS-Plus bits. Suitable for impact and unstressed drilling. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min⁻¹ from a switch. Impact energy of 2,9 J and optimal drilling range of 8 – 18 mm in concrete. Max. drilling capacity of 26 mm in concrete.



TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER	HR2600
NO LOAD SPEED	800W
IMPACT	0-1200min? ¹
MAX. DRILLING DIAMETER IN WOOD	0-4600min? ¹
MAX. DRILLING DIAMETER IN CONCRETE	32mm
MAX. DRILLING DIAMETER IN STEEL	26mm
OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE	13mm
IMPACT ENERGY	8-18mm
DRILLING DIAMETER WITH TCT CORE BIT	2,4J
POWER SUPPLY CORD	68mm
SIDE GRIP	2,5m
DEPTH GAUGE (2)	Yes
SOUND POWER LEVEL (LWA)	Yes
SOUND PRESSURE LEVEL (LPA)	102dB(A)
NOISE UNCERTAINTY (K FACTOR)	91dB(A)
VIBRATION LEVEL (3 AXES), DRILLING	3dB(A)
VIBRATION LEVEL (3 AXES), IMPACT DRILLING	=2,5m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	15,0m/s ²
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	1,5m/s ²
PRODUCT DIMENSIONS (L X W X H):	3,0-3,4kg
	361x77x209mm

USER BENEFITS

- 2-mode operation for "Rotation Only" or "Hammering with Rotation"
- 360° swivel side handle
- Double insulated
- Ergonomic handle
- Variable speed

Link to Product page - <https://makitauae.com/product/hr2600-combination-hammer/>