



Combination Hammer

HR2630

800 W • SDS-Plus • 26 mm • 2,9 J

Professional three-mode rotary hammer

Efficient combination hammer compatible with SDS-Plus bits. Suitable for impact and unstressed drilling, plus chipping. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min⁻¹ from a switch. Impact energy of 2,9 J and optimal drilling range of 8 – 18 mm in concrete. Max. drilling capacity of 26 mm in concrete.



TECHNICAL

SPECIFICATIONS

| | |
|---|-------------------------|
| MAXIMUM OUTPUT POWER | HR2630 |
| NO LOAD SPEED | 800W |
| IMPACT | 0-1200min? ¹ |
| MAX. DRILLING DIAMETER IN WOOD | 0-4600min? ¹ |
| MAX. DRILLING DIAMETER IN CONCRETE | 32mm |
| MAX. DRILLING DIAMETER IN STEEL | 26mm |
| OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE | 13mm |
| IMPACT ENERGY | 8-18mm |
| DRILLING DIAMETER WITH TCT CORE BIT | 2,9J |
| POWER SUPPLY CORD | 68mm |
| SIDE GRIP | 4,0m |
| DEPTH GAUGE (2) | Yes |
| SOUND POWER LEVEL (LWA) | Yes |
| SOUND PRESSURE LEVEL (LPA) | 102dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 91dB(A) |
| VIBRATION LEVEL (3 AXES), DRILLING | 3dB(A) |
| VIBRATION LEVEL (3 AXES), IMPACT DRILLING | ?2,5m/s ² |
| VIBRATION: CHISELLING | 15,0m/s ² |
| VIBRATION UNCERTAINTY (K FACTOR) | 9,5m/s ² |
| WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003) | 1,5m/s ² |
| PRODUCT DIMENSIONS (L X W X H): | 2,8-3,3kg |
| EAN | 361x77x209mm |
| | 88381687300 |

USER BENEFITS

- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- Depth gauge for increased drilling consistency
- The rubber coating on the handle ensures a firm working grip
- Torque limiter stops rotation if bit jams for increased operator safety and enhanced motor protection
- Variable speed trigger allows the user to adjust discharge rate

Link to Product page - <https://makitauae.com/product/hr2630-combination-hammer/>