



# Combination Hammer

## HR2630

800 W • SDS-Plus • 26 mm • 2,9 J

### Professional three-mode rotary hammer

Efficient combination hammer compatible with SDS-Plus bits. Suitable for impact and unstressed drilling, plus chipping. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min<sup>-1</sup> from a switch. Impact energy of 2,9 J and optimal drilling range of 8 – 18 mm in concrete. Max. drilling capacity of 26 mm in concrete.



## TECHNICAL

## SPECIFICATIONS

MAXIMUM OUTPUT POWER	HR2630
NO LOAD SPEED	800W
■ IMPACT	0-1200min? <sup>1</sup>
MAX. DRILLING DIAMETER IN WOOD	0-4600min? <sup>1</sup>
MAX. DRILLING DIAMETER IN CONCRETE	32mm
MAX. DRILLING DIAMETER IN STEEL	26mm
OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE	13mm
IMPACT ENERGY	8-18mm
DRILLING DIAMETER WITH TCT CORE BIT	2,4J
POWER SUPPLY CORD	68mm
SIDE GRIP	4,0m
DEPTH GAUGE (2)	Yes
SOUND POWER LEVEL (LWA)	Yes
SOUND PRESSURE LEVEL (LPA)	102dB(A)
NOISE UNCERTAINTY (K FACTOR)	91dB(A)
VIBRATION LEVEL (3 AXES), DRILLING	3dB(A)
VIBRATION LEVEL (3 AXES), IMPACT DRILLING	?2,5m/s <sup>2</sup>
VIBRATION: CHISELLING	15,0m/s <sup>2</sup>
VIBRATION UNCERTAINTY (K FACTOR)	9,5m/s <sup>2</sup>
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	1,5m/s <sup>2</sup>
PRODUCT DIMENSIONS (L X W X H):	2,8-3,3kg
EAN	361x77x209mm
	88381687300

## USER BENEFITS

- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- Depth gauge for increased drilling consistency
- The rubber coating on the handle ensures a firm working grip
- Torque limiter stops rotation if bit jams for increased operator safety and enhanced motor protection
- Variable speed trigger allows the user to adjust discharge rate

Link to Product page - <https://makitauae.com/product/hr2630-combination-hammer/>