



Combination Hammer

HR2661

800 W • SDS-Plus • 26 mm • 2,9 J

Three-mode, anti-vibration rotary hammer with dust bag and quick-change chuck for professional use

A robust combination hammer for SDS-Plus bits with an AVT anti-vibration system and HEPA self dust collection. Suitable for impact and unstressed drilling and chipping. 800 W output and speed can be adjusted between 0 and 1 200 min⁻¹ from a switch. Impact energy of 2,9J and optimal drilling range of 8 – 18 mm in concrete, with a max. capacity of 26 mm.



TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER	HR2661
NO LOAD SPEED	800W
■ IMPACT	0-1100min ^{?1}
MAX. DRILLING DIAMETER IN WOOD	0-4500min ^{?1}
MAX. DRILLING DIAMETER IN CONCRETE	32mm
MAX. DRILLING DIAMETER IN STEEL	26mm
OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE	13mm
IMPACT ENERGY	8-18mm
DRILLING DIAMETER WITH TCT CORE BIT	2,2J
ADAPTED FOR SDS-PLUS BITS	68-80mm
POWER SUPPLY CORD	Yes
PLASTIC CARRYING CASE	2,5m
SOUND POWER LEVEL (LWA)	Yes
SOUND PRESSURE LEVEL (LPA)	101dB(A)
NOISE UNCERTAINTY (K FACTOR)	90dB(A)
VIBRATION LEVEL (3 AXES), DRILLING	3dB(A)
VIBRATION LEVEL (3 AXES), IMPACT DRILLING	?2,5m/s ²
VIBRATION: CHISELLING	9,5m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	6,0m/s ²
PRODUCT WEIGHT	1,5m/s ²
PRODUCT DIMENSIONS (L X W X H):	3,3-4,4kg
EAN	666x89x228mm
	88381845991

USER BENEFITS

- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- Depth gauge for increased drilling consistency
- Double insulated
- HEPA filter removes particles with an efficiency rating of 99.75%
- Rear handle with soft rubber grip, ergonomically designed for comfortable operation
- Variable speed trigger allows operator to adjust speed based on materials or application

Link to Product page - <https://makitauae.com/product/hr2661-combination-hammer/>