



Rotary Hammer

■ HR2800

800 W • SDS-Plus • 28 mm • 2,9 J

Professional two-mode rotary hammer

An efficient rotary hammer for SDS-Plus bits. Suitable for impact and unstressed drilling. 800 W output and speed can be adjusted between 0 and 1 100 min⁻¹ from a switch. Impact energy of 2,9 J and optimal drilling range of 8 – 20 mm in concrete. Max. drilling capacity of 28 mm in concrete.



TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER	HR2800
NO LOAD SPEED	800W
■ IMPACT	0-1100min? ¹
MAX. DRILLING DIAMETER IN WOOD	0-4500min? ¹
MAX. DRILLING DIAMETER IN CONCRETE	32mm
MAX. DRILLING DIAMETER IN STEEL	28mm
OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE	13mm
IMPACT ENERGY	8-20mm
POWER SUPPLY CORD	2,8J
PLASTIC CARRYING CASE	2,5m
SIDE GRIP	Yes
SOUND POWER LEVEL (LWA)	Yes
SOUND PRESSURE LEVEL (LPA)	100dB(A)
NOISE UNCERTAINTY (K FACTOR)	89dB(A)
VIBRATION LEVEL (3 AXES), DRILLING	3dB(A)
VIBRATION LEVEL (3 AXES), IMPACT DRILLING	?2,5m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	20,0m/s ²
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	1,5m/s ²
PRODUCT DIMENSIONS (L X W X H):	3,2kg
	314x89x225mm

USER BENEFITS

- 2-mode operation for "Rotation Only" or "Hammering with Rotation"
- Double insulated
- One-touch sliding chuck for easy bit installation and removal
- Rear handle with soft rubber grip, ergonomically designed for comfortable operation

Link to Product page - <https://makitauae.com/product/hr2800-rotary-hammer/>