



Combination Hammer

HR2810

800 W • SDS-Plus • 28 mm • 2,9 J

Professional three-mode rotary hammer

An efficient combination hammer for SDS-Plus bits. Suitable for impact and unstressed drilling, plus chipping. 800 W output and speed can be adjusted between 0 and 1 100 min⁻¹ from a switch. Impact energy of 2,8 J and optimal drilling range of 8 – 20 mm in concrete. Max. drilling capacity of 28 mm in concrete.



TECHNICAL

SPECIFICATIONS

| | |
|---|-------------------------|
| MAXIMUM OUTPUT POWER | HR2810 |
| NO LOAD SPEED | 800W |
| ■ IMPACT | 0-1100min ⁻¹ |
| MAX. DRILLING DIAMETER IN WOOD | 0-4500min ⁻¹ |
| MAX. DRILLING DIAMETER IN CONCRETE | 32mm |
| MAX. DRILLING DIAMETER IN STEEL | 28mm |
| OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE | 13mm |
| IMPACT ENERGY | 8-20mm |
| POWER SUPPLY CORD | 2,8J |
| SIDE GRIP | 2,5m |
| DEPTH GAUGE (2) | Yes |
| SOUND POWER LEVEL (LWA) | Yes |
| SOUND PRESSURE LEVEL (LPA) | 100dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 89dB(A) |
| VIBRATION LEVEL (3 AXES), DRILLING | 3dB(A) |
| VIBRATION LEVEL (3 AXES), IMPACT DRILLING | ?2,5m/s ² |
| VIBRATION: CHISELLING | 20,0m/s ² |
| VIBRATION UNCERTAINTY (K FACTOR) | 15,5m/s ² |
| WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003) | 1,5m/s ² |
| PRODUCT DIMENSIONS (L X W X H): | 3,8kg |
| EAN | 88381083829 |

USER BENEFITS

- Depth gauge for increased drilling consistency
- Double insulated
- Lock-on button for user convenience during longer work periods
- Recessed lock-on button for continuous operation
- Torque limiting clutch engineered to minimize gear damage by automatically disengaging gears if the bit binds
- Torque Limiting Clutch Engineered to Prevent Gear Damage

Link to Product page - <https://makitauae.com/product/hr2810-combination-hammer/>