



Rotary Hammer

HR4501C

1 350 W • SDS-Max • 45 mm • 12.5 J

Powerful dual-action combi hammer for heavy-duty use

Efficient 1 350 W combi hammer for SDS-MAX blades. Masonry drilling capacity of 45 mm and impact energy of 12,5 J. With its drilling and chipping functions, this tool is an ideal choice for renovation and building work.



TECHNICAL

SPECIFICATIONS

| | |
|--|----------------------------|
| MAXIMUM OUTPUT POWER | HR4501C |
| NO LOAD SPEED | 1350W |
| ■ IMPACT | 130-280min? ¹ |
| MAX. DRILLING DIAMETER IN CONCRETE | 1250-2750min? ¹ |
| OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE | 45mm |
| IMPACT ENERGY | 20-35mm |
| DRILLING DIAMETER WITH TCT CORE BIT | 10,1J |
| POWER SUPPLY CORD | 125mm |
| PLASTIC CARRYING CASE | 5,0m |
| SIDE GRIP | Yes |
| DEPTH GAUGE (2) | Yes |
| SOUND POWER LEVEL (LWA) | Yes |
| SOUND PRESSURE LEVEL (LPA) | 105dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 94dB(A) |
| VIBRATION LEVEL (3 AXES), IMPACT DRILLING | 3dB(A) |
| VIBRATION: CHISELLING | 16,0m/s ² |
| VIBRATION LEVEL (3 AXES), CHISELLING WITH D-TYPE SIDE HANDLE | 12,5m/s ² |
| VIBRATION UNCERTAINTY (K FACTOR) | 12,5m/s ² |
| WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003) | 1,5m/s ² |
| PRODUCT DIMENSIONS (L X W X H): | 8,2-8,4kg |
| EAN | 458x121x288mm |
| | 88381084970 |

USER BENEFITS

- Dust-protected tool holder
- Kontrollleuchte meldet Betriebsbereitschaft und KohlebÄ¼rstenverschleiß
- Torque limiting clutch engineered to minimize gear damage by automatically disengaging gears if the bit binds
- (blank)

Link to Product page - <https://makitauae.com/product/hr4501c-rotary-hammer/>