



Rotary Hammer

HR5202C

1 510 W • SDS-Max • 52 mm • 21J

Dual-action combi hammer for demanding professional use

Efficient 1 510 W combi hammer for SDS-MAX blades. Masonry drilling capacity of 52 mm and impact energy of 21 J. With its drilling and chipping functions, this tool is an ideal choice for renovation and building work.



TECHNICAL

SPECIFICATIONS

| | |
|--|----------------------------|
| MAXIMUM OUTPUT POWER | HR5202C |
| NO LOAD SPEED | 1510W |
| IMPACT | 150-310min? ¹ |
| MAX. DRILLING DIAMETER IN CONCRETE | 1100-2250min? ¹ |
| OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE | 52mm |
| IMPACT ENERGY | 25-40mm |
| DRILLING DIAMETER WITH TCT CORE BIT | 19,1J |
| POWER SUPPLY CORD | 160mm |
| PLASTIC CARRYING CASE | 4,0m |
| SIDE GRIP | Yes |
| SOUND POWER LEVEL (LWA) | Yes |
| SOUND PRESSURE LEVEL (LPA) | 110dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 99dB(A) |
| VIBRATION LEVEL (3 AXES), IMPACT DRILLING | 3dB(A) |
| VIBRATION: CHISELLING | 17,0m/s ² |
| VIBRATION LEVEL (3 AXES), CHISELLING WITH D-TYPE SIDE HANDLE | 10,5m/s ² |
| VIBRATION UNCERTAINTY (K FACTOR) | 10,5m/s ² |
| WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003) | 1,5m/s ² |
| PRODUCT DIMENSIONS (L X W X H): | 10,9-11,1kg |
| EAN | 599x134x287mm |
| | 88381677592 |

USER BENEFITS

Link to Product page - <https://makitauae.com/product/hr5202c-rotary-hammer/>