



# Reciprocating Saw

## JR3050T

1 010 W • 0 – 2 800 min<sup>-1</sup> • 28 mm

### Reliable reciprocating saw for professionals

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1 010 W motor, stroke length of 28 mm and stroke rate of 0 – 2 800 min<sup>-1</sup> with continuous control from the switch. Quick-release blade attachment.



### TECHNICAL

### SPECIFICATIONS

MAXIMUM OUTPUT POWER	1010 W
IMPACT	0 - 2800 min <sup>-1</sup>
POWER SUPPLY CORD	2,5 m
SOUND POWER LEVEL (LWA)	99 dB(A)
SOUND PRESSURE LEVEL (LPA)	88 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	15,0 m/s <sup>2</sup>
VIBRATION UNCERTAINTY (K FACTOR)	2,5 m/s <sup>2</sup>
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	3,3 kg
PRODUCT DIMENSIONS (L X W X H):	452 x 97 x 170 mm
EAN	88381061407
LENGTH OF STROKE	28 mm
MAX. CUTTING CAPACITY IN WOOD (90°)	255 mm
JIG SAW BLADES	Yes

### USER BENEFITS

Link to Product page - <https://makitauae.com/product/jr3050t-reciprocating-saw/>