

Reciprocating Saw

JR3050T

1 010 W • 0 − 2 800 min?¹ • 28 mm

Reliable reciprocating saw for professionals

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1 010 W motor, stroke length of 28 mm and stroke rate of $0-2\,800$ min-1 with continuous control from the switch. Quick-release blade attachment.



TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER IMPACT

POWER SUPPLY CORD
SOUND POWER LEVEL (LWA)
SOUND PRESSURE LEVEL (LPA)
NOISE UNCERTAINTY (K FACTOR)
VIBRATION LEVEL (3 AXES)
VIBRATION UNCERTAINTY (K FACTOR)
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE

01/2003)
PRODUCT DIMENSIONS (LX W X H):

PRODUCT DIMENSIONS (L X W X H):

EAN
LENGTH OF STROKE
MAX. CUTTING CAPACITY IN WOOD (90°)
JIG SAW BLADES

0 - 2800 min?¹ 2,5 m 99 dB(A) 88 dB(A) 3 dB(A) 15,0 m/s² 2,5 m/s²

1010 W

3,3 kg 452 x 97 x 170 mm 88381061407

28 mm 255 mm Yes

USER BENEFITS

Link to Product page - https://makitauae.com/product/jr3050t-reciprocating-saw/