



Reciprocating Saw

JR3051TK

1 200 W • 0 – 3 000 min⁻¹ • 30 mm

Reliable reciprocating saw for professionals

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1 200 W motor, stroke length of 30 mm and stroke rate of 0 – 3 000 min⁻¹ with continuous control from the switch. Quick-release blade attachment.



TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER	1200 W
IMPACT	0 - 3000 min ⁻¹
POWER SUPPLY CORD	4,0 m
SOUND POWER LEVEL (LWA)	99 dB(A)
SOUND PRESSURE LEVEL (LPA)	88 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	19,5 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	3,3 kg
PRODUCT DIMENSIONS (L X W X H):	447 x 97 x 176 mm
EAN	88381891905
LENGTH OF STROKE	30 mm
MAX. CUTTING CAPACITY IN WOOD (90°)	255 mm
MAX. CUTTING CAPACITY IN STEEL PIPE	130 mm

USER BENEFITS

- Large 2-finger trigger for added convenience
- Toolless blade change for fast blade installation and removal
- Variable speed trigger for precise cutting in a wide variety of applications

Link to Product page - <https://makitauae.com/product/jr3051tk-reciprocating-saw/>