



# Reciprocating Saw AC

## JR3061T

1,250 W • 0 – 3,000 min<sup>-1</sup> • 32 mm

### Rugged reciprocating saw with three-stage pendulum action

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1,250 W motor, stroke length of 32 mm and stroke rate of 0 – 3,000 min<sup>-1</sup> with continuous control from the switch. Three-stage pendulum action and quick-release blade attachment.



## TECHNICAL

### SPECIFICATIONS

MAXIMUM OUTPUT POWER	1250 W
IMPACT	0 - 3000 min <sup>-1</sup>
POWER SUPPLY CORD	4,0 m
SOUND POWER LEVEL (LWA)	99 dB(A)
SOUND PRESSURE LEVEL (LPA)	88 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	16,5 m/s <sup>2</sup>
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	3,8 kg
PRODUCT DIMENSIONS (L X W X H):	487 x 95 x 177 mm
BARCODE	0088381867009
LENGTH OF STROKE	32 mm
MAX. CUTTING CAPACITY IN WOOD (90°)	255 mm
JIG SAW BLADES	Yes

### USER BENEFITS

Link to Product page - <https://makitauae.com/product/jr3061t-reciprocating-saw/>