



Reciprocating Saw

JR3070CT

1 510 W • 0 – 2 800 min⁻¹ • 32 mm

Rugged reciprocating saw with three-stage pendulum action and anti-vibration system

A professional reciprocating saw with AVT (anti-vibration technology) for spark-free cutting of metal and demolition work. An efficient 1 510 W motor, stroke length of 32 mm and stroke rate of 0 – 2 800 min⁻¹ with continuous control from the switch. Three-stage pendulum action and quick-release blade attachment.



TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER	1 510 W
IMPACT	0 - 2800 min ⁻¹
POWER SUPPLY CORD	2,5 m
SOUND POWER LEVEL (LWA)	99 dB(A)
SOUND PRESSURE LEVEL (LPA)	88 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	4,6 kg
PRODUCT DIMENSIONS (L X W X H):	485 x 99 x 181 mm
EAN	88381061322
LENGTH OF STROKE	32 mm
MAX. CUTTING CAPACITY IN WOOD (90°)	255 mm
ORBITAL ACTION	Yes
VIBRATION LEVEL (3 AXES), CUTTING CHIPBOARD	9,5 m/s ²

USER BENEFITS

- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- Double insulated
- Lock-on feature for continuous operation
- Variable speed trigger allows operator to adjust speed based on materials or application

Link to Product page - <https://makitauae.com/product/jr3070ct-reciprocating-saw/>