



## Metal Shear

### JS1601

380 W • 4 500 min<sup>-1</sup>

**A high capacity metal shear with a radius of 250 mm**

A metal shear for straight and curved cuts with a radius of 250 mm, cuts a clean-edged strip from the middle. Cutting capacity of 2,5 mm for aluminium and 1,6 mm for steel. A motor capacity of 380 W and a stroke rate of 4 500 min<sup>-1</sup>.



## TECHNICAL

### SPECIFICATIONS

MAXIMUM OUTPUT POWER	380 W
IMPACT	4500 min <sup>-1</sup>
POWER SUPPLY CORD	2,5 m
SOUND POWER LEVEL (LWA)	88 dB(A)
SOUND PRESSURE LEVEL (LPA)	77 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	9,5 m/s <sup>2</sup>
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	1,4 kg
PRODUCT DIMENSIONS (L X W X H):	320 x 70 x 78 mm
EAN	88381609074
CUTTING CAPACITY MILD STEEL (UP TO 400N/MM <sup>2</sup> )	1,6 mm
CUTTING CAPACITY STAINLESS STEEL (UP TO 600N/MM <sup>2</sup> )	1,2 mm
MIN. INTERNAL CUTTING RADIUS	250 mm
MIN. EXTERNAL CUTTING RADIUS	254 mm
CUTTING CAPACITY ALUMINUM (UP TO 200N/MM <sup>2</sup> )	2,5 mm
CUTTING CAPACITY STAINLESS STEEL (UP TO 800N/MM <sup>2</sup> )	0,8 mm

- Compact and lightweight design

### USER BENEFITS

Link to Product page - <https://makitauae.com/product/js1601-metal-shear/>