



## Metal Shear

### JS1602

380 W • 4 000 min<sup>-1</sup>

#### Handy, high-capacity metal shear

A metal shear for straight and curved cuts with a radius of 30 mm, cuts a clean-edged strip from the middle. A high cutting capacity of 2,5 mm for aluminium and 1,6 mm for steel. A motor capacity of 380W and a stroke rate of 4 000 min<sup>-1</sup>.



## TECHNICAL

### SPECIFICATIONS

MAXIMUM OUTPUT POWER	380 W
IMPACT	4000 min <sup>-1</sup>
POWER SUPPLY CORD	2,5 m
SOUND PRESSURE LEVEL (LPA)	79 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	7,0 m/s <sup>2</sup>
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	1,6 kg
PRODUCT DIMENSIONS (L X W X H):	255 x 74 x 146 mm
EAN	88381634113
CUTTING CAPACITY MILD STEEL (UP TO 400N/MM <sup>2</sup> )	1,6 mm
CUTTING CAPACITY STAINLESS STEEL (UP TO 600N/MM <sup>2</sup> )	1,2 mm
MIN. EXTERNAL CUTTING RADIUS	30 mm
CUTTING CAPACITY ALUMINUM (UP TO 200N/MM <sup>2</sup> )	2,5 mm
CUTTING CAPACITY STAINLESS STEEL (UP TO 800N/MM <sup>2</sup> )	0,8 mm

### USER BENEFITS

Link to Product page - <https://makitauae.com/product/js1602-metal-shear/>