



Slide Compound Saw

LS1018LN

1 430 W • 260 mm • 4 300 min?¹

Efficient and accurate saw with a laser for high-capacity applications

0



■ TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER 1430 W
 POWER SUPPLY CORD 25.5 m
 SOUND POWER LEVEL (LWA) 103 DB(A)
 SOUND PRESSURE LEVEL (LPA) 77 DB(A)
 NOISE UNCERTAINTY (K FACTOR) 1.5
 VIBRATION LEVEL (3 AXES) 1.2 m/s²
 VIBRATION UNCERTAINTY (K FACTOR) 1.5
 WEIGHT WITHOUT CABLE (EPTA-PROCEDURE) 20.6 kg
 01/2009 325 x 536 x 633 mm
 PRODUCT DIMENSIONS (L X W X H): 325 x 536 x 633 mm
 EAN 4300 min?¹
 NO LOAD SPEED 2550 rpm
 BLADE DIAMETER 260 mm
 MAX. BEVEL RANGE (LEFT) 45°
 LASER CLASS 1
 CAPACITY 210°
 CAPACITY 35°
 BLADE 47 / 60°
 MAX. MITRE RANGE (LEFT) 47°

USER BENEFITS

- Dust bag for a cleaner work environment
- Electric brake for maximum productivity
- Ergonomic rubberized D-handle design for better fit and added comfort
- Large Cutting Capacity in a Compact Design and Less Weight
- Large precision machined aluminum base supports material for more efficient cutting
- Less weight and compact design for job site portability
- Oversized trigger switch for better fit, added comfort and easier operation
- See-through blade guard system for greater visibility of blade and line of cut
- Soft start feature for smooth start-ups

Link to Product page - <https://makitauae.com/product/ls1018ln-slide-compound-saw/>