



# Slide Compound Saw

## LS1018LN

1 430 W • 260 mm • 4 300 min?<sup>1</sup>

Efficient and accurate saw with a laser for high-capacity applications

0



### TECHNICAL

### SPECIFICATIONS

- MAXIMUM OUTPUT POWER 1430 W
- POWER SUPPLY CORD 25 m
- SOUND POWER LEVEL (LWA) 107 dB(A)
- SOUND PRESSURE LEVEL (LPA) 107 dB(A)
- NOISE UNCERTAINTY (K FACTOR) 1.5
- VIBRATION LEVEL (3 AXES) 1.2 m/s<sup>2</sup>
- VIBRATION UNCERTAINTY (K FACTOR) 1.5
- WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2005) 2.5 kg
- PRODUCT DIMENSIONS (L X W X H): 338 x 108 x 415 mm
- EAN 4300 min?<sup>1</sup>
- NO LOAD SPEED 2600 rpm
- BLADE DIAMETER 260 mm
- MAX. BEVEL RANGE (LEFT) 45°
- LASE CLASS 1
- CAPACITY 260 mm
- CAPACITY 260 x 45 mm
- BLADE 47 / 60°
- MAX. MITRE RANGE (LEFT) 45°

### USER BENEFITS

- Dust bag for a cleaner work environment
- Electric brake for maximum productivity
- Ergonomic rubberized D-handle design for better fit and added comfort
- Large Cutting Capacity in a Compact Design and Less Weight
- Large precision machined aluminum base supports material for more efficient cutting
- Less weight and compact design for job site portability
- Oversized trigger switch for better fit, added comfort and easier operation
- See-through blade guard system for greater visibility of blade and line of cut
- Soft start feature for smooth start-ups

Link to Product page - <https://makitauae.com/product/ls1018ln-slide-compound-saw/>