



# Rotary Hammer

## HR3011FCWJ



### Product Description

1050 W • SDS-Plus • 30 mm • 3,6 J  
**Professional three-mode rotary hammer**  
Powerful rotary hammer for SDS-Plus blades with unique AVT anti-vibration system. The machine can be drilled without impact or with impact and has a spike function. The motor power is 1050 W and the speed is adjustable from 0-840min-1. The device achieves a 3.6J impact force. The maximum capacity for drilling into concrete is 30 mm.

### Product Features

- High performance SDS-PLUS drill hammer; concrete max. 30 mm.
- Impact drilling, non-impact drilling and spike function
- The rubber coating on the handle ensures a firm working grip
- LED light illuminates the work site
- AVT (Anti-Vibration Technology) ensures extra-low vibration performance

### Barcode

88381896726

### Product Specifications

|                                             |                            |
|---------------------------------------------|----------------------------|
| Vibration Level (3 axes), Drilling          | ≤ 2,5 m/s <sup>2</sup>     |
| Drilling diameter with TCT core bit         | 80 mm                      |
| Max. Drilling Diameter in Steel             | 13 mm                      |
| Max. Drilling Diameter in Wood              | 32 mm                      |
| Vibration Level (3 axes), Impact Drilling   | 10,8 m/s <sup>2</sup>      |
| Optimum Drilling Diameter Range in Concrete | 8.0-16 mm                  |
| Sound Pressure Level                        | 90 dB(A)                   |
| Power Supply Cord                           | 2,5 m                      |
| Impact Energy                               | 3,9 J                      |
| Continuous Input Power                      | 1050 W                     |
| Vibration Uncertainty (K Factor)            | 1,5 m/s <sup>2</sup>       |
| Vibration: Chiselling                       | 9,7 m/s <sup>2</sup>       |
| Product Dimensions (L x W x H):             | 369 x 98 x 242 mm          |
| Impacts per Minute (IPM)                    | 0 - 4500 min <sup>-1</sup> |
| Sound Power Level (LWA)                     | 101 dB(A)                  |
| Weight Without Cable (EPTA)                 | 4,8 kg                     |
| Noise Uncertainty (K Factor)                | 3 dB(A)                    |

|                                           |                               |
|-------------------------------------------|-------------------------------|
| <b>Max. Drilling Diameter in Concrete</b> | 30 mm                         |
| <b>Adapted for SDS-PLUS bits</b>          | 1                             |
| <b>Tool Category</b>                      | Hammer Drilling and Chiseling |
| <b>No load speed</b>                      | 0 - 840 min <sup>-1</sup>     |

More info

<https://makitauae.com/product/rotary-hammer-hr3011fcwj/>