



Plunge Router

RP1800

220V: 2 300W • 127V: 1 650W • 12 mm

Powerful professional plunge router

A powerful plunge router with a 220V: 2 300W / 127V: 1 650W motor for professional use. Equipped with depth adjustment with micro control. 12 mm collet. Suitable for use as a fixed base router.



TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER	1850 W
POWER SUPPLY CORD	4,0 m
SOUND POWER LEVEL (LWA)	97 dB(A)
SOUND PRESSURE LEVEL (LPA)	86 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	4 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	6,0 kg
PRODUCT DIMENSIONS (L X W X H):	155 x 294 x 312 mm
EAN	88381099271
NO LOAD SPEED	22.000 min ⁻¹
LENGTH OF STROKE	0 - 70 mm
PLUNGE CAPACITY	0 - 70 mm
MAX. COLLET CAPACITY	12 mm
BASE DIMENSIONS	170 x 155 mm

USER BENEFITS

- External suction directly on the cutter
- Linear ball bearing ensures smooth dipping of the milling cutter
- Locking button for quick adjustment
- MAKPAC 4 content: suspension rail, adapter for the guide rail and 12-piece cutting cartridge
- Rip fence with 0.1 mm adjustable accuracy
- Three-position preselected revolver control

Link to Product page - <https://makitauae.com/product/rp1800-plunge-router/>