



## Circular Saw

### SP6000

1 300 W • 2 000 – 5 800 min<sup>?1</sup> • 165 mm

#### Precise plunge cut circular saw

A precise plunge cut circular saw for accurate cutting. Ideal for installing furnishing or decking. Recommended for use with a guide rail. A motor capacity of 1 300 W and cutting capacity of 56mm. Speed can be adjusted between 2 000 – 5 800 min<sup>-1</sup>.



### TECHNICAL

### SPECIFICATIONS

MAXIMUM OUTPUT POWER	1300 W
POWER SUPPLY CORD	2,5 m
SOUND POWER LEVEL (LWA)	92 dB(A)
SOUND PRESSURE LEVEL (LPA)	103 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	? 2,5 m/s <sup>2</sup>
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	4,1 kg
PRODUCT DIMENSIONS (L X W X H):	341 x 225 x 250 mm
EAN	88381078115
NO LOAD SPEED	2200 - 6400 min <sup>?1</sup>
BLADE DIAMETER	165 mm
BORE SIZE (ARBOR DIAMETER)	20 mm
MAX. CUTTING DEPTH AT 48°	38 mm
MAX. CUTTING DEPTH AT 90°	56 mm
MAX. CUTTING DEPTH AT 45°	40 mm
MAX. BEVEL RANGE (LEFT)	1 / 48 °

### USER BENEFITS

Link to Product page - <https://makitauae.com/product/sp6000-circular-saw/>