



Impact Driver XGT®

TD002G

40V max • 1/4" • 220 Nm • 0 – 3,700 min?¹

Extremely compact impact driver powered by 40Vmax XGT Li-Ion battery.

Powerful brushless Impact Driver. The maximum torque is 220 Nm and the machine has multiple operation modes for a wide range of applications; 4-speed power selection and 6 Assist modes.



TECHNICAL

SPECIFICATIONS

| | |
|-----------------------------------|---|
| IMPACT | 0 - 1400 / 2600 / 3600 / 4600 min? ¹ |
| SOUND POWER LEVEL (LWA) | 105 dB(A) |
| SOUND PRESSURE LEVEL (LPA) | 94 dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 3 dB(A) |
| VIBRATION UNCERTAINTY (K FACTOR) | 1,5 m/s ² |
| PRODUCT WEIGHT | 1,0 kg |
| PRODUCT DIMENSIONS (L X W X H): | 119 x 86 x 252 mm |
| EAN | 0088381767804 |
| NO LOAD SPEED | 0 - 1100 / 2100 / 3200 / 3700 min? ¹ |
| BRUSHLESS MOTOR | Yes |
| MAX FASTENING TORQUE IMPACT DRILL | 220 Nm |
| MAX FASTENING TORQUE HARD/SOFT | 170 / 20 Nm |
| TIGHTENING CAPACITY STANDARD BOLT | M5 - M16 |
| CAPACITY MACHINE SCREW | M4 - M8 |
| VIBRATION LEVEL (3 AXES) | 12,9 m/s ² |
| TOOL WEIGHT WITH BATTERY (EPTA) | 1,7 - 2,9 kg |
| NOMINAL BATTERY VOLTAGE | 40 V |
| VOLTAGE XGT | Yes |
| DRIVING SHANK | 1/4 " |
| DRIVE SQUARE | 1/4 " |

USER BENEFITS

- Ergonomically designed handle with soft grip provides increased comfort on the job
- Electric brake for maximum productivity and increased operator safety
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to Product page - <https://makitauae.com/product/td002g-impact-driver-xgt/>