



Angle Impact Wrench CXT®

TL065DZ

12V max • 3/8" • 60 Nm • 0 – 2 000 min?¹



■ TECHNICAL

Angle impact wrench for tight spaces

A compact and light 3/8" angle impact wrench. An angle head height of 53 mm makes this tool an ideal choice for tight spaces. A long paddle switch and handy LED light for added comfort. Tool only, battery and charger not included.

SPECIFICATIONS

| | |
|--|----------------------------|
| IMPACT | 0 - 3000 min? ¹ |
| SOUND POWER LEVEL (LWA) | 101 dB(A) |
| SOUND PRESSURE LEVEL (LPA) | 90 dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 3 dB(A) |
| VIBRATION UNCERTAINTY (K FACTOR) | 1,5 m/s ² |
| PRODUCT DIMENSIONS (L X W X H): | 361 x 66 x 86 mm |
| NO LOAD SPEED | 0 - 2000 min? ¹ |
| CXT BATTERY | Yes |
| BATTERY PROTECTION | Yes |
| MAX FASTENING TORQUE IMPACT DRILL | 60 Nm |
| TIGHTENING CAPACITY STANDARD BOLT | M4 - M12 |
| CAPACITY MACHINE SCREW | M4 - M8 |
| TIGHTENING CAPACITY HIGH TENSILE BOLT | M4 - M8 |
| VIBRATION LEVEL (3 AXES), FASTENING BOLT | 18 m/s ² |
| TOOL WEIGHT WITH BATTERY (EPTA) | 1,2 -1,6 kg |
| ANGLE LENGTH | 53 mm |
| NOMINAL BATTERY VOLTAGE | 12 V |
| DRIVE SQUARE | 3/8 " |

USER BENEFITS

- Body model - delivered without battery and charger.
- LED light illuminates the work site
- The rubber coating on the handle ensures a firm working grip

Link to Product page - <https://makitauae.com/product/tl065dz-angle-impact-wrench-cxt/>